

Multi-Technology Air Purifier

Active Photocatalytic TiO₂ + Silver Ion Oxidation

4XNP Ion/Plasma Generator

Germicidal UV Light















Eliminates Odors

Germs

UV Lamp Warranty:

Allergen

Stops Reduction Bio-growth

Removes Smoke

Design

Design and technologies

Base Operation:	Active photocatalytic oxidation (PCO)
Additional technologies:	Dual-band germicidal UV, bi-polar ionization, UV surface and air disinfection
UV lamp:	Dual-band 10"
Catalyst surface area:	200 sq inches
Catalyst reactor length:	10.5" with twin active layers
Construction:	Stainless steel and aluminum
PCO coating for odor reduction and air stream disinfection:	Exclusive patented titanium dioxide/silver (Ag) blend PCO coating. Silver ions reduce pathogens in the air and on surfaces.
PCO adjustability:	Yes, with a 4" adjustment range, never limits UV disinfection levels.
Electronics /Lamp Monitoring:	Electronic lamp operation monitor with end of lamp life notification
Ionization for particulate reduction and surface disinfection:	4 needlepoint electrode, negative and positive ion generator (4XNP)
Expandability:	Yes, unit powers an optional remote UV lamp or additional PCO module
System Warranty:	Lifetime

2 years














Active PCO TiO₂ + Silver Ion Oxidation / 4XNP Plasma Ionization / Germicidal UV Light

The **Solaris®** Whole House Air Purifier eradicates germs, allergens, odors and VOC/ chemical pollution using multiple technologies. Dual-band germicidal UV light inactivates bacteria, viruses and allergens and powers photocatalytic oxidation that breaks down odors, VOCs and other airborne chemical pollutants. The 4XNP ion/plasma generator enhances air sterilization while causing microscopic particulates to gather in groups for easy capture in filtration. The innovative and patented titanium dioxide based photocatalytic formulation is enhanced with silver ions that inhibit bio-growth on surfaces.









Solaris Specifications

Model SLX1024 Operating Range Up to 3300 sq ft (adjustable) Electrical 24VAC 23VA Voltage Source Range 24 to 240 VAC (Multi-tap transformer) Overall Depth 14.5" — Dimensions — PCO Module 3.75"w x 3.75h" x 10.5"d

Power Module 7.25"w x 5.25"h x 4"d

Quick Connector for

connection to Solaris

UV Light Upgrade

Need a UV light on the coil? Save time and expense by adding an optional Ultravation® EZ UV Light germicidal UV light for HVAC interior surface disinfection. The UV lamp is powered directly by the Solaris purifier. The kit includes a high intensity Ultravation® T3™ UV lamp, quick connector and hardware.

Model EZLIGHT12-6P EZLIGHT17-6P Description 12" Ultravation T3 lamp 17" Ultravation T3 lamp _____ Included features

6 ft. connecting cable

UV shield 6 ft. cable Quick Connector internal / external mount bracket and magnet









EPA establishment number: 074725-VT-00



Ultravation® EZ UV Light